# **BookletChart**<sup>TM</sup>




# North Shore of Long Island Sound -Stratford to Sherwood Point

**NOAA Chart 12369** 

A reduced-scale NOAA nautical chart for small boaters When possible, use the full-size NOAA chart for navigation.



- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker



# Published by the National Oceanic and Atmospheric Administration National Ocean Service Office of Coast Survey

<u>www.NauticalCharts.NOAA.gov</u> 888-990-NOAA

# What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

# What is a BookletChart<sup>™</sup>?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at <a href="http://www.NauticalCharts.NOAA.gov">http://www.NauticalCharts.NOAA.gov</a>.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

# **Notice to Mariners Correction Status**

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at <a href="http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=123">http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=123</a> 69.



(Selected Excerpts from Coast Pilot)
Bridgeport Harbor, on the north side of
Long Island Sound north-northwestward of
Stratford Shoal (Middle Ground) Light and
about 52 miles from New York, consists of
two widely separated units. The main
harbor and its branches serve the east and
central portions of the city of Bridgeport,
and Black Rock Harbor and its tributaries
serve the western part. Black Rock Harbor
and Cedar Creek are described under
separate headings.

**Prominent features.**—The large red and white horizontally banded stack of a powerplant on Tongue Point is the most prominent landmark in this area. Other prominent landmarks include several church spires, the

radio towers at Pleasure Beach, and Bridgeport Harbor Light 13A. An aerolight about 1.3 miles northwestward of Stratford Point can be seen from offshore

**Bridgeport Harbor Light 13A** (41°09'24"N., 73°10'47"W.), 50 feet above the water, is shown from a black skeleton tower with small white house, on a black base, on the west side of the entrance channel near the end of the west breakwater.

Channels.—From deep water in Long Island Sound the dredged channel extends north-northeastward between two converging breakwaters into the main harbor, and thence into the three tributaries, Johnsons Creek, Yellow Mill Channel, and Pequonnock River. Federal project depth is 35 feet in the main channel to just below the Connecticut Turnpike bridge. (See Notice to Mariners and latest edition of the chart for depths.) A powerplant is at **Tongue Point**. A privately dredged channel leads from the main channel to the powerplant's offshore oil wharf on the south side of the point. In 1980, the channel, except for a 17-foot depth on the southwesterly side of the widener, had a reported controlling depth of about 26 feet; depths of 31 to 37 feet are reported alongside the wharf. Another privately dredged channel, used by barges, leads from the main channel to the powerplant's facilities on the east side of the point. In 2009, the controlling depth in the channel was 13.5 feet.

Yellow Mill Channel is entered through a dredged channel that leads for about 0.8 mile north-northeastward from just above the first bend in the main channel to the head of the creek. Flats, largely bare at low water, are on both sides of the channel. The Stratford Avenue highway bridge about 0.3 mile above the entrance has a bascule span with a clearance of 11 feet. (See 117.1 through 117.59 and 117.225, chapter 2, for drawbridge regulations.) About 0.1 mile above the bascule bridge is a fixed turnpike bridge with a clearance of 39 feet. Depths at the wharves are 8 to 15 feet.

Pequonnock River, the most westerly of the tributaries, is easily clearance of the bridges over Pequonnock River follow: Connecticut Turnpike, fixed, 300 yards, 60 feet; Stratford Avenue, vertical-lift, 500 yards, 8 feet down and 68 feet up, Peck Railroad bridge, bascule, 0.5 mile, 26 feet; highway bridge, bascule, 0.7 mile, 4 feet. (See 117.1 through 117.59 and 117.219, chapter 2 for drawbridge regulations.) The bridgetender at the railroad bridge monitors VHF-FM channel 13; call sign KU-6033. The draw spans at the Congress Street bridge, 0.6 mile, have been removed due to deterioration but the approach spans have been retained.

Anchorages.—Bridgeport Harbor has three anchorage areas inside the breakwaters. An anchorage is on the east side of the main channel northwestward of Pleasure Beach. A second is on the west side of the channel south of Tongue Point and a third runs parallel to the west side of the main channel from Tongue Point to Steel Point. The rest of the harbor area consists of broad and shallow sand flats. Vessels seeking shelter from strong northerly winds sometimes anchor off the entrance; the holding ground is good.

A general anchorage is in Johnsons Creek.

**Dangers.**—The entrance is clear, and the only dangers are the previously discussed shoals on the east, south of Stratford Point, and on the west, the Penfield Reef shoals.

**Currents.**—The velocity of flood or ebb is about 0.7 knot in the entrance between the breakwaters. (See the Tidal Current Tables for predictions.) Inside the harbor the currents are generally weak.

# U.S. Coast Guard Rescue Coordination Center 24 hour Regional Contact for Emergencies

RCC Boston Commander

1st CG District (617) 223-8555 Boston, MA



NOAA's navigation managers serve as ambassadors to the maritime community.

They help identify navigational challenges facing professional and recreational mariners, and provide NOAA resources and information for safe navigation. For additional information, please visit nauticalcharts.noaa.gov/service/navmanagers

To make suggestions or ask questions online, go to *nauticalcharts.noaa.gov/inquiry*. To report a chart discrepancy, please use *ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx*.

# Lateral System As Seen Entering From Seaward on navigable waters except Western Rivers



10

09'

# SOUNDINGS IN FEET



UNITED STATES - EAST COAST CONNECTICUT

# NORTH SHORE OF LONG ISLAND SOUND

# STRATFORD TO SHERWOOD POINT

Mercator Projection Scale 1:20,000 at Lat. 41°07'

North American Datum of 1983 (World Geodetic System 1984)

SOUNDINGS IN FEET AT MEAN LOWER LOW WATER

For Symbols and Abbreviations see Chart No. 1

Additional information can be obtained at nauticalcharts.noaa.gov.

### AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

### CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners. During some winter months or when endan-gered by ice, certain aids to navigation are replaced by other types or removed. For details could School Guard Light List. see U.S. Coast Guard Light List.

### RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

### CAUTION

Mariners are warned to stay clear of the pro-tective riprap surrounding navigational light structures shown thus:

Racing buoys within the limits of this chart are not shown hereon. Information may be obtained from the U.S. Coast Guard District Offices as racing and other private buoys are not all listed in the U.S. Coast Guard Light List.

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

# SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 2 for important supplemental information.

В4

B5

### HORIZONTAL DATUM

The horizontal Entone datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.347 northward and 1.595' eastward to acree with this chart to agree with this chart.

### CAUTION

CAUTION

Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.

Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

Station positions are shown thus:

(Accurate location) o(Approximate location)

# CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.

SUBMARINE PIPELINES AND CABLES Charted submarine pipelines and submarine cables and submarine pipeline and cable areas are shown as:

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and sub-marine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when

0

# New York, NY Meriden, CT Montville, CT Riverhead, NY WXJ-42 KHB-47 WXM-80

high elevations.

BASCULE BRIDGE CLEARANCES

For bascule bridges, whose spans do no open to a full upright or vertical position, unlimited vertical clearance is not available for the entir charted horizontal clearance

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be

as much as 100 nautical miles for stations a

0

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (foll free), or to the nearest U.S. Coast Guard facility if telephone com-munication is impossible (33 CFR 153).

HEIGHTS

Heights in feet above Mean High Water.

**AUTHORITIES** Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers and U.S. Coast Guard.

NOTE A

Navigation regulations are published in Chapter 2, U.S.
Coast Pilot 2. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning
the regulations may be obtained at the Office of the Commander, 1st Coast Guard District in Boston, MA or at the
Office of the District Engineer, Corps of Engineers in
Concord, MA.

Refer to charted regulation section numbers.

NOTE Z NO-DISCHARGE ZONE, 40 CFR 140

NO-DISCHARGE ZONE, 40 CFR 140
This chart falls entirely within the limits of a No-Discharge Zone (NDZ). Under the Clean Water Act, Section 312, all vessels operating within a No-Discharge Zone (NDZ) are completely prohibited from discharging ary swage, treated or untreated, into the waters. All vessels with an installed marine santation device (NSD) that are navigating, moored, anchored, or docked within a NDZ must have the MSD disabled to prevent the overboard discharge of sewage (treated or untreated) or install a holding tank. Regulations for the NDZ are contained in the U.S. Coast Pilot. Additional information concerning the regulations and requirements may be obtained from the Environmental Protection Agency (EPA) web site: http://www.epa.gov/owow/oceans/regulatory/vessel\_sewage/.

## SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, United States Coast Pilot,

1900-1939 NOS Surveys Pre-1900 NOS Surveys


SOURCE


full bottom coverage partial bottom coverage partial bottom coverage


Joins page 8

NOS Surveys


Note: Chart grid lines are aligned with true north.
















Note: Chart grid lines are aligned with true north.












Note: Chart grid lines are aligned with true north.










10

Note: Chart grid lines are aligned with true north.








12369


This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notce to Manners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand comer. Chart updates corected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts nose.gov.

Last Correction: 12/28/2015. Cleared through: LNM: 2516 (6/21/2016), NM: 2716 (7/2/2016), CHS: 0616 (6/24/2016)

Note: Chart grid lines are aligned with true north.








Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

Note: Chart grid lines are aligned with true north.







# VHF Marine Radio channels for use on the waterways:

**Channel 6** – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

**Channel 16** – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other

vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here. Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

**Getting and Giving Help** — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

# **Distress Call Procedures**

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of

Emergency; Number of People on Board.

- · Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!



NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.

http://www.nws.noaa.gov/nwr/

# **Quick References**

Nautical chart related products and information — http://www.nauticalcharts.noaa.gov

Interactive chart catalog — http://www.charts.noaa.gov/InteractiveCatalog/nrnc.shtml

Report a chart discrepancy — http://ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx

Chart and chart related inquiries and comments — http://ocsdata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs

Chart updates (LNM and NM corrections) — http://www.nauticalcharts.noaa.gov/mcd/updates/LNM\_NM.html

Coast Pilot online — http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm

Tides and Currents — http://tidesandcurrents.noaa.gov

Marine Forecasts — http://www.nws.noaa.gov/om/marine/home.htm

National Data Buoy Center — http://www.ndbc.noaa.gov/

NowCoast web portal for coastal conditions — http://www.nowcoast.noaa.gov/

National Weather Service — http://www.weather.gov/

National Hurrican Center — http://www.nhc.noaa.gov/

Pacific Tsunami Warning Center — http://ptwc.weather.gov/

Contact Us — http://www.nauticalcharts.noaa.gov/staff/contact.htm



For the latest news from Coast Survey, follow @NOAAcharts



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.